




## FDN 59 Port Integrated Routing Closure

### A Length with Basket

#### Features and Benefits

- Maximum 144 fibre splice capacity when using SC-B tray
- 58 round ports and 1 oval port
- Positive fibre management to ensure consistent 30mm minimum fibre bend radii throughout
- Fibre storage basket for loop through applications
- Bi-directional fibre routing
- Accommodates SC, SC-B and SE trays
- Maximum 12 splices per tray
- Splitter accommodation
- Cablelok compatible for all port sizes
- Quick release cover
- Optional pressure release valve



FDN IR 59 Port A-Length Closure with Basket

FDN 59 Port Base Port Configuration

#### Technical Description

The FDN 59 Port Integrated Routing (IR) A Length closure with basket is supplied with a Polypropylene base. The base configuration of 58 round ports and 1 oval port covers a cable diameter range of 1.7 – 29.0mm when using Cablelok mechanical seals and 6.0 – 35.0mm when using heatshrink.

The mounting system is manufactured from Grade 304 stainless steel and the backplane is an aluminium extrusion which can accommodate up to 6 IR SE trays or 12 IR SC/SC-B trays or a combination of SE, SC and SC-B trays. The position of the mounting system allows easy access for the routing of the fibre on to the trays and the basket provides storage

space for the storage of fibre loops. The trays and fibre optic routing module are white which makes it easy to see the colour of the fibre elements as they are routed through the positive fibre management system. Fibre slot retaining blocks guide fibre elements in to the IR system, the foam pad on the retainer is partially cut through to accommodate a range of fibre counts.

All IR system cover plates are coloured blue identifying them as removable parts allowing access to the fibre, the fibre slot retaining block and tray retaining clips are coloured red to aid in identification if they are dropped.

TYPE	Width D1 (mm)	Width D2 (mm)	Length L (mm)	Base Type	Tray Type	Tray Quantity	Splice Protector Type	Basket Size	Article-No.
FDNIR-AXBCXW	312	222	455	Cablelok, Heatshrink	IR SC	12	3A	Small	857-00492
FDNIR-AXBCXN	312	222	455	Cablelok, Heatshrink	IR SC-B	12	3A	Small	857-00895
FDNIR-AXBCWX	312	222	455	Cablelok, Heatshrink	IR SE	6	3A	Small	857-00491
FDNIR-AXBCXX	312	222	455	Cablelok, Heatshrink	Not supplied	-	-	Small	857-00490

Products listed are for standard configurations, other configurations and splice insert types are available - see Page 176

#### Content of Set/Kit

- FDN 59 Port IR Base
- A-Length Cover (Dome)
- Quick Release Clamp
- Sealing 'O' Ring
- Fibre Storage Basket
- Fibre Optic Routing Module
- Fibre Optic Storage Unit
- Fibre Optic Storage Unit Lid
- Fibre Slot Entry Module
- Fibre Slot Retaining Block
- Reusable Cable Ties
- Tray Lid
- Tray Tool
- Anchor Fixing Kit (3)
- Spiral Binding
- Isopropyl Alcohol Wipes
- Desiccant
- Installation Guide
- Marker Kit
  - Red Marker 1 - 12
  - Green Marker 1 - 12