SAFETY-TECHNICAL INFORMATION



1 av 1

JETTING MICRO DUCT LUBE

MICRO DUCT LUBE is a special lubricant for ducts up to 12 mm inside diameter, used previous to blowing of mini/micro fibre/cables.

MICRO DUCT LUBE is water based and can be used down to -15 degrees C. It leaves a very tiny film of lubricant, reduces drastically the friction, static electricity, and adheres perfectly to the fibre/cable and to the duct surface.

Use:

- 1. Clean the inside of the duct by blowing a sponge slowly thru the duct.
- 2. Shake the bottle before using.
- 3. Pre lubricate by:
 - Place a sponge as far into the duct according to the table on the bottle.
 - Fill the suggested lubricant into the duct.
 - Place one or two sponges in the end and blow this thru slowly.
 - For best result, leave the lubricate to dry for 5- 10 min
- 4. The duct is now ready for fibre / cable blowing.

Quantities:

15 ml x 1.000 mt for diameter 12 mm (about 15 cm full Duct) 10 ml x 1.000 mt for diameter 8 mm (about 20 cm full Duct) 5 ml x 1.000 mt for diameter 4 mm (about 30 cm full Duct)

Technical Specifications:

Aspect White liquid tiny viscosity

Odour characteristic

Viscosity 30 sec. Ford cup diam. mm 4 at 20C°

Specific gravity 1,030 +- 0,03 gr/cm3

pH 7,5 +- 0,5

Inflammability non infiammabile Temperature -15° + 70° C.

Biodegradability yes

Toxic The product is not toxic.

HS Code 3403.9900

Country of origin Italy
Art. No 34030

JETTING AB, Sweden, www.jetting.se