


Miniduct Optical Cable

Cable Design

IEC/EN 60794



- 72FO version illustrated, not to scale -

- **Central Strength Member (CSM):** glass fibres reinforced plastic material (FRP).
- **Loose Tube:** thermoplastic material containing 6 or 12 optical fibres and filled with a suitable water tightness compound.
- **Filler Elements:** thermoplastic rods, when needed.
- **Identification Thread**
- **Stranding:** loose tubes, SZ stranded around the CSM.
- **Binding elements:** aramid yarns
- **Longitudinal Water Tightness:** water swellable materials (dry core).
- **Outer Sheath:** HDPE.

This optical cable is designed for duct installation by blowing technique.

Technical data

No. of Fibres		12	24	36	48	60	72	96
Design	-	1x12	2x12	3x12	4x12	5x12	6x12	8x12
Number of fillers	-	5	4	3	2	1	-	-
Tube diameter - ϕ	mm	1.55						
CSM/Enlargement - ϕ	mm	1.6/-						
Sheath thickness	mm	0.4						
Cable diameter - ϕ	mm	5.8						
Cable weight	Kg/Km	30						

Min. bending radius	mm	Under Maximum Tension: 20xCable- ϕ		Without Tension: 15xCable- ϕ	
Temperature range	°C	Transport & Storage: -40 \rightarrow +70		Installation: -15 \rightarrow +55	
				Operation: -30 \rightarrow +60	

Main characteristics

Test	Standard	Value	Requirement*
Tensile strength	IEC 60794-1-21-E1	1000N, 1 min.	$\Delta\alpha$ reversible
Cable Sheath Abrasion	IEC 60794-1-21-E2A	500 cycles, 4N	No penetration, optical continuity
Cable Marking Resistance	IEC 60794-1-21-E2B/2	100 cycles, 4N	Legible marking
Crush	IEC 60794-1-21-E3	3 x 500N/100mm, 5min	$\Delta\alpha \leq 0.05$ dB under test, no damage
Impact	IEC 60794-1-21-E4	3J, 3 impacts, R=300 mm	$\Delta\alpha \leq 0.1$ dB / fibre, no damage
Repeated Bending	IEC 60794-1-21-E6	R=20xOD, 100N, 25 cycles	No damage of cable`s elements
Cable Torsion	IEC 60794-1-21-E7	$\pm 180^\circ$, 2 m, 5 cycles, 20N	$\Delta\alpha \leq 0.1$ dB / fibre, no damage
Kink	IEC 60794-1-21-E10	20xOD	No kink
Cable Bend	IEC 60794-1-21-E11	R=20xOD, 3 cycles, 4 turns	$\Delta\alpha \leq 0.1$ dB / fibre, no damage
Temperature Cycling	IEC 60794-1-22-F1	-30 \rightarrow 60°C, 2 cycles, 24h/cycle	$\Delta\alpha \leq 0.15$ dB/Km, reversible
Aging test	IEC 60794-1-22-F1	T= 85 °C, 96h	$\Delta\alpha \leq 0.1$ dB/Km, reversible
Water Penetration	IEC 60794-1-22-F5B	1m sample, 1m water, 24h	No water penetration

* values for single-mode fibres, all optical measurements performed at 1550 nm

Optical Characteristics

See the attached cabled optical fibre data sheet.

Identification

Fiber colors:

No.	1	2	3	4	5	6	7	8	9	10	11	12
Colour	blue	orange	green	brown	slate	white	red	black	yellow	violet	rose	aqua

Tube Colors:

Fibre Count	Elements							
	1	2	3	4	5	6	7	8
1x12	BL12T	NF	NF	NF	NF	NF	-	-
2x12	BL12T	OR12T	NF	NF	NF	NF	-	-
3x12	BL12T	OR12T	GN12T	NF	NF	NF	-	-
4x12	BL12T	OR12T	GN12T	BN12T	NF	NF	-	-
5x12	BL12T	OR12T	GN12T	BN12T	SL12T	NF	-	-
6x12	BL12T	OR12T	GN12T	BN12T	SL12T	WH12T	-	-
8x12	BL12T	OR12T	GN12T	BN12T	SL12T	WH12T	RD12T	BK12T

where: BL12T = Blue tube with 12 fibers, OR12T = Orange tube with 12 fibers, GR12T = Green tube with 12 fibers, BN12T = Brown tube with 12 fibers, WH12T = White tube with 12 fibers, SL12T = Slate tube with 12 fibers, RD12T = Red tube with 12 fibers, BK12T = Black tube with 12 fibers, NF = Natural Filler.

Sheath Color:

The outer sheath color is black.

Sheath Marking:

The outer sheath is marked in 1 meter intervals by ink jet method as follows:

PRYSMIAN(S) yyyy OPTICAL CABLE A-DQ(ZN)2Y t x 12 <fiber type> ANSI zzzz

where: yyyy = year of production, t = no. of tubes, zzzz = sequential length mark, <fiber type> = i.e. G.652D, G.655C, G.657A2, etc.

Logistic

Packing:

Wooden drums with protection.

Delivery Lengths: 2000 ± 100 m; 4000 ± 200 m; 6000 ± 300 m.

Other lengths available upon agreement, up to a maximum of 10% of the total number of cable lengths could be shorter than nominal values.

© PrysmianGroup 2022, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by PrysmianGroup: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of PrysmianGroup. The information is believed to be correct at the time of issue. PrysmianGroup reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorized by PrysmianGroup.